



FIGURE 1
RECOMMENDED FRONT CUT-OUT

FIGURE 2
ALTERNATE FRONT CUT-OUT

FIGURE 3
ALTERNATE FRONT CUT-OUT

KEY INTERLOCK

KEY INTERLOCK SPECIFICATIONS FOR SWITCHES EQUIPPED WITH KEY INTERLOCK PROVISIONS ARE:
 .375 BOLT PROJECTION WHEN WITHDRAWN
 - KIRK TYPE B
 - SUPERIOR TYPE B6003

REV. 3 1-15-96 JAE, CORRECTION IN REC'D CUT-OUT (7.5 WAS 7)
 REV. 2 11-6-95 JAE, NEW RECOMMENDED CUT-OUT ADDED
 REV. 1 12-16-91 WCE, OPTIONAL CLOSING SOLENOID ADDED

NOTE:
 THIS DRAWING SUPERSEDES DRAWINGS NUMBERED 0-1065 & 0-1069.

SHUNT TRIP OPERATOR TYPE ST-5 (VL, VLB, SL & SLB)		
SCALE:	APPROVED BY:	DRAWN BY WCE
DATE: 10-1-91		REVISED 3
boltswitch, inc. CRYSTAL LAKE, ILLINOIS		DRAWING NUMBER 0-1090A